



DULUX EASYCLEAN PLUS SHEEN-FINISH

A990 Line (WATERBASED)

PRODUCT INFORMATION

PRODUCT NAME	Dulux EasyClean Plus
Product Code	A990 Line
DESCRIPTION	Dulux EasyClean Plus is a premium quality washable emulsion with a sheen finish.
USAGE	Dulux EasyClean Plus is suitable for all normal interior wall masonry surfaces including brickwork, plaster, cement, asbestos and wallboards.
BENEFITS	The KidProof Technology makes cleaning easy. This keeps colours beautiful for longer.
PACK SIZE	1, 5 and 18L
COLOR RANGE	Refer to Colour Inspirations.

PERFORMANCE GUIDE

FILM PROPERTIES Water Resistance	Will tolerate the levels of atmospheric humidity present in normal interior environments and will withstand vigorous washing. Excellent scrubability and stain resistance. Extremely hardwearing and excellent adhesion.
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal conditions is 11-12 m ² /litre.

PRODUCT DATA

COMPOSITION (nominal)	Pigment : Lightfast Non-Lead Pigments and Mineral Extenders. Binder : Acrylic Emulsion. Solvent : Water.
VOLUME SOLIDS	White 41% (nominal), other colours will vary.

APPLICATION

THINNING Brush or Roller	For sealing new or bare surfaces thin with up to 1 part of clean water to 5 parts of paint (20%). For normal use, thinning is usually not necessary. If required, should not exceed 1 part of clean water to 10 parts of paint (10%).
Conventional Spray Airless Spray	Add up to 1 part of clean water to 5 parts of paint (20%). Ready to use.
SPRAY RECOMMENDATIONS Conventional spray Airless Spray	Satisfactory through most equipment. A typical set up for airless spray application would be a minimum working pressure on paint of 140 kg/cm ² (2000 lb/sq in) with a spray tip size 0.38mm (15 thou) and a spray tip angle 65°.
DRYING TIMES Touch Dry Recoat	Single coat at standard thickness: Dependent on temperature and humidity. 1 - 2 hours.
CLEANING UP	Clean all equipment with clean water immediately after use.

PRE-APPLICATION

SURFACE PREPARATION	Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be thoroughly rubbed down using a suitable abrasive paper and dusted off. Treat areas affected by mould, fungi or algae with Dulux Fungicidal Wash (A980-19260). If after thorough preparation, surfaces remain powdery, seal with one coat of an appropriate Primer (see below). It should not be applied on areas where moisture reading (as measured by Protimeter) exceeds 17%. These wall should be left to dry further.	
SYSTEM INFORMATION	PRIMER (1 COAT)	FINISH (2 COATS)
Powdery Surfaces	Dulux Adhesion Promoting Interior Wall Primer	
Alkaline and New Surfaces	Dulux Exterior & Interior Wall Sealer	Dulux EasyClean Plus
Normal, Sound Surfaces	No Primer Required.	

PRECAUTION

HEALTH, SAFETY AND ENVIRONMENT INFORMATION	Product Safety Data Sheet available upon request
---	--

Any advice, recommendations, information, assistance or service provided by Akzo Nobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service provided by Akzo Nobel Paints is provided without expressed or implied warranties.

Akzo Nobel Paints (Malaysia) Sdn Bhd

(Formerly known as ICI Paints (Malaysia) Sdn Bhd)

For further details on Product Data Sheet, kindly contact:

Customer Care Department

Tel: 1-800-88-9338 Website: www.dulux.com.my Email: customercare.my@akzonobel.com

A BRAND FROM
AkzoNobel